

# Datasheet

# HARVEST collection

September 2025

## 1. PRODUCT DESCRIPTION

Bring rural charm to your project with Harvest. These planks have a rustic and authentic look that adds warmth and character to any setting, from a cozy garden to a country-style facade.

## 2. DIMENSIONS & WEIGHT



|                                 |                |                |               |
|---------------------------------|----------------|----------------|---------------|
| <b>Size</b>                     | 200x20x3000 mm | 140x20x3000 mm | 70x20x3000 mm |
| <b>Weight per board</b>         | 5.73 kg        | 3.78 kg        | 1.62 kg       |
| <b>Weight per m<sup>2</sup></b> | 10.60 kg       | 10.5 kg        | 11.4 kg       |

### INSTALLATION METHOD: CLICK SYSTEM

|                                 |           |           |           |
|---------------------------------|-----------|-----------|-----------|
| <b>Clips per m<sup>2</sup></b>  | 25 pieces | 37 pieces | 42 pieces |
| <b>Working width</b>            | 183 mm    | 123 mm    | 53 mm     |
| <b>Boards per m<sup>2</sup></b> | 1.85 mm   | 2.78 mm   | 7.01 mm   |
| <b>M<sup>2</sup> per boards</b> | 0.54      | 0.36      | 0.159     |

### INSTALLATION METHOD: SCREW FASTENING

|                                 |             |             |             |
|---------------------------------|-------------|-------------|-------------|
| <b>Screws per m<sup>2</sup></b> | 12 pieces   | 19 pieces   | 47 pieces   |
| <b>Working width</b>            | 175.5 mm    | 115.5 mm    | 47.5 mm     |
| <b>Boards per m<sup>2</sup></b> | 1.90 pieces | 2.89 pieces | 7.02 pieces |
| <b>M<sup>2</sup> per board</b>  | 0.53        | 0.35        | 0.14        |

## 3. MATERIAL PROPERTIES

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Material</b>                     | Polyvinyl chloride (advanced PVC) |
| <b>Surface finish</b>               | Wood grain                        |
| <b>UV resistance</b>                | Yes (UV stabilised)               |
| <b>Water absorption</b>             | <0,1%                             |
| <b>Fire class</b>                   | B- s2, d0 (EN 13501-1)            |
| <b>Linear expansion coefficient</b> | -80 x 10 <sup>-6</sup> /°C        |
| <b>Temperature range</b>            | -30°C tot +70°C                   |
| <b>Warranty</b>                     | 30 years                          |

## 4. INSTALLATION

|                                 |   |
|---------------------------------|---|
| <b>Recommended beam spacing</b> | 400-450 mm (center to center)   |
| <b>Fastening</b>                | Invisible Cortex fastening, Click-Fastening, grad or keraloc                              |
| <b>Expansion joint</b>          | The boards should be installed without any gaps at the ends (no expansion joint required) |

**Please note:** Dimensions and weights may vary.


**The information provided may vary; current information and test results can be found on the website.**

### DIMENSIONS


70 mm



140 mm




200 mm




### WORKING WIDTH SCREWED


47.5 mm



115.5 mm



175.5 mm



### Kerama Group B.V.

Braillestraat 10  
2652 XV Berkel en Rodenrijs  
The Netherlands  
+31 (0) 174 788 350

[WWW.KERAMAGROUP.NL](http://WWW.KERAMAGROUP.NL) | [INFO@KERAMAGROUP.NL](mailto:INFO@KERAMAGROUP.NL)

